




BestSolv™ 7300

Non-Flammable Engineered Solvent



Technical Data Sheet

Introduction

BestSolv™ 7300, also known as 1,1,1,2,2,3,4,5,5,5-Decafluoro-3-methoxy-4-(trifluoromethyl) pentane (C₇H₃F₁₃O), is an exact molecule, single isomer replacement for 3M® Novec® 7300. The hydrofluoroether (HFE) solvent is VOC exempt and used in thermal heat transfer, semiconductor manufacturing, and light cleaning or as a rinsing agent.

It is ideal for use in sensitive electronic environments due to its non-flammable and non-conductive / dielectric properties. Along with effective thermal heat transfer and solvent cleaning capabilities, it has low toxicity, a low global warming potential (GWP), and zero ozone depletion (ODP).

BestSolv™ 7300 is also an effective cleaning agent, making it suitable for electronics, precision optics, and fingerprinting removal. With its high boiling point and low surface tension, it is well-suited for use in vapor degreasing applications as a pure substance or as an azeotropic component.

Features and Benefits

Applications

- Non-Conductive
- Non-Flammable
- Low Surface Tension
- Low Viscosity
- Zero ODP
- No/low Surface Residue
- High Dielectric Strength
- Good Thermal Stability
- VOC Exempt

- Thermal / Heat Transfer For Electronic Equipment
- Immersion / Data Center Cooling
- Semiconductor Cleaning, Dry Etching, Wafer Testing, Packaging Testing

- Deposition Carrier Fluid
- Fluorocarbon Lubricant Carrier Fluid
- Replacement for:
 - HFCs
 - PFCs
 - PFPEs

- Heavy Cleaning as Azeotrope with 1,2 trans
 - Oils
 - Greases
 - Waxes
- Light Cleaning / Rinse as Neat
 - Fluoropolymers
 - Particulate

Industries Served

Physical and Chemical Properties

- Aerospace
- Military
- Electronic
- Semiconductor
- Optical
- Medical device



Distributed Exclusively By:

Best Technology

- ☎ (612) 392-2414
- ✉ Chemicals@BestTechnologyInc.com
- 🌐 www.BestSolv.com

CAS #	132182-92-4
Molecular Weight	350 g/mol
Liquid Density	1.66 g/mL
Boil Point	98 °C / 208 °F
Freezing / Pour Point	-38 °C / -36 °F
Dielectric Strength 0.1" Gap	>25kV
Volume resistivity	10 ¹¹ Ohm-cm

Vapor Pressure (25°C)	44mmHg
Specific Heat	1.1 kJ/(kg-K)
Exposure TWA	100 ppm
Surface Tension	15 dyne/cm
Thermal Conductivity	0.06 W/m-K
GWP	<300
ODP	0

Data compiled from published information. Not for specification purposes



BestSolv™ 7300



Storage and Handling

Based on Pensky-Martens Closed Cup (ASTM D93) or Tag Closed Cup (ASTM D56) methods, BestSolv™ 7300 exhibits no flash point and is not classified as flammable by OSHA or DOT. As with almost all halogenated solvents, flammability limits exist in the presence of a high ignition energy source.

BestSolv™ 7300 is best stored inside a clean, dry area and out of direct sunlight or other heat sources. It is thermally stable and will not oxidize or degrade during storage under normal conditions. To prevent leakage or potential rupture of the container due to contraction / expansion and pressure changes, do not store below 32 °F (0 °C) or above 90 °F (32 °C)

Environmental Properties

- SNAP EPA accepted substitute for ozone depleting substances
- VOC Exempt
- Not subject to SARA Title III (EPCRA) reporting regulation
- Non hazardous air pollutant (HAP) / Not regulated under NESHAP
- Low global warming potential (GWP)
- Low / zero ozone depletion potential (ODP)

Health and Safety

Reference the SDS for details on:

- Individual chemical components
- Disposal
- Transportation
- Regulatory requirements
- Other information

Materials Compatibility

BestSolv™ 7300 is compatible with common metals, most alloys and some polymers / elastomers.

Metals: Aluminum, Copper*,
Monel, Nickel, Stainless Steel

Plastics: ABS, Acrylics (PMMA), Polyethylene,
Polypropylene, Polycarbonate

Elastomers: EPDM, Natural
Rubber, Polyurethane

*Heat aging resulted in slight surface oxidation of copper. Some swelling of PTFE and silicone rubber.

Initial compatibility testing on non-production parts is recommended. Material compatibility should always be performed via testing with specific contaminants under process-specific cleaning conditions.

Product Use / Warranty

All information contained in this document is based on data believed to be reliable but the accuracy or completeness thereof is not guaranteed and are made without representation or warranty. Many factors can affect the use, performance, time and environmental conditions in a particular application. User is responsible for evaluation to determine whether it is fit for a particular purpose and application and products discussed are sold without warranty, expressed or implied, in law or fact.

We shall not be liable for any injury, loss or damage direct or consequential regardless of the legal theory asserted, including warranty, contract, negligence or strict liability arising out of use or the inability to use the product. If the product is defective within the warranty period, your exclusive remedy and seller's sole obligation will be, at seller's option, to replace the product or refund the purchase price.

NO OTHER WARRANTIES ARE OFFERED, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.